



TABLE OF CONTENTS

- Introduction
- Quality Policy
- Available Tests
- Equipment Introduction
- Scopes
- Contact



"WHO WE ARE"

FOR ALL WHO KEEP THE WORLD MOVING

MFTBC

As an integral part of **Daimler Truck AG**, Mitsubishi Fuso

Truck and Bus Corporation has served over 170 markets around the world in terms of product development, parts sourcing and production, with the aim to provide the best value to our customers.



MFTBC QM

Quality Management dept.
encompasses many cross
functional roles across all
Truck Asia operations,
projects and governance.
We work to uphold quality
standards, conscious warranty
spending and efficient field
fixes to exceed customer
expectations.

"WHO WE ARE"

QM MATERIAL LAB

"Not just a testing Lab, but your reliable Service Provider"



Founded in 1970, we has been providing various services for material related testing, investigations and consultation.



Accredited by ISO17025:2017, we are committed to provide reliable, confidential, accurate, and valid testing result.



By utilizing modern and calibrated devices, and a team of highly qualified experts, we aim to serve our customers the best solution for the whole value chain.

DAIMLER

Mitsubishi Fuso Truck and Bus Corporation.

Material Laboratory Quality Policy

MFTBC Material Lab is committed to provide impartial, confidential, reliable, accurate and precise test results to the customers by adapting good laboratory practices through trained and competent Laboratory staff and by implementing Quality Management System consistently as per ISO/IEC 17025:2017 guidelines.

Material Lab complies to inspection & Failure Investigation as per national & International Standards & also customer requirements by encouraging active participation of Laboratory personnel to continually improve the effectiveness of Quality Management System.

MFTBC Material Lab assesses the risks associated with Lab activities and takes opportunities for improving the management system.

Hanieh Abbaspour Head of Supplier Quality Fuso

Mitsubishi Fuso Truck and Bus Corporation

Japan 1st July 2022

Daimler Trucks Asia









Certificate of Accreditation

International Accreditation Japan (IAJapan) hereby accredits the following conformity assessment body as a testing laboratory of Japan National Laboratory Accreditation System.

Accreditation Identification: JNLA 220415JP Testing

Name of Conformity Assessment Body: Mitsubishi Fuso Truck and Bus Corporation,

QM Materials Lab

Name of Legal Entity: Mitsubishi Fuso Truck and Bus Corporation

Location of Conformity Assessment Body: 10, Ohkura-cho, Nakahara-ku, Kawasaki-shi, Kanagawa


211-8522, JAPAN

Scope of Accreditation: as the following pages Accreditation Requirement: ISO/IEC 17025:2017*

* The relevant accreditation requirements described in the JNLA

Accreditation Scheme Document are also applied.

Effective Date of Accreditation: 2022-03-23 Expiry Date of Accreditation: 2026-03-22 Date of Initial Accreditation: 2022-03-23



SAKAMOTO Kozo

Chief Executive, International Accreditation Japan (IAJapan)

National Institute of Technology and Evaluation

ISO SCOPES

JIS Z 2244-1
JIS Z 2245
JIS Z 2243-1
JIS Z 2371

International Accreditation Japan (IAJapan) is a laboratory accreditation body which has signed MRAs of ILAC (International Laboratory Accreditation Cooperation) and APAC (Asia Pacific Accreditation Cooperation).

MRA requirements are, in addition to relevant international standards and guides, requirements for participation in perficiency testing programs, surveillance and reassessment, and the policy for the traceability of measurement for MRA purpose.

⁻ This laboratory fluifills ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This acceptation means this laboratory meets both the technical competence requirements and management system requirements that are necessary for it to consistently deliver technically valid test results and calibrations (refer to joint ISO-ILAC-LAF Communiqué dated April 2017).

⁻ The latest accreditation information is publicly available on LAJapan Website as an accreditation certificate.

METAL

NON-METAL

Failure Analysis

Hardness

Tensile and Compression Strength

Elemental Analysis (Chemical Composition)

Residual Stress Test

Metallography Test

Macrostructure Observation

Depth of Decarburization

Case Depth

Crack Observation

Elemental Analysis

Failure Analysis
Material Identification

Hardness

Elemental Analysis (Chemical Composition)

Peeling Test

Tensile Strength

Heat Aging

Impact Resistance

Chemical Resistance

Environmental Cyclic Test

Flexural test

Glass Fiber Content Measurement

AVAILABLE TESTS

CORROSION

Salt Spray Test

Combined Cyclic Corrosion Test

Painting Thickness

Plating Thickness

Impact Test

Coating Hardness

Painting Adhesion

Alkalin/ Acid Resistance Test

CONTAMINATION

Visual Observation Elemental Analysis

Material Analysis

Particle Size Distribution

Universal Hardness Tester



Application

Measure the hardness in different scales such as HRA, HRB, HRC, Hv, HBW.

Range

60-650 HBW; 100-850 HV; 20-88 HRA/20-100 HRBW/20-70 HRC

Micro Vickers Hardness Tester




Application

Measure the hardness of metals, ceramics, composites, plastic; useful for very thin materials or measuring the surface of parts and the hardness of different phases of a structure.

Range

100-850 HV 0.025 - 2kg

Digital Microscope



Application

Used for the fracture surface observation.

Magnification

1X - 540X

Metallographic Microscope



Application

Used for observing the microstructure; inspecting grain size, different phases of a structure, coating thickness, etc.

Magnification

10X - 1000X

Scanning Electron Microscope (SEM)



Application

Produces images of a sample by scanning the surface with a focused beam of electrons; produces various signals contain information about the surface topography and composition of the sample.

Magnification

High magnification mode: 20X - 500000X

Optical Emission Spectroscopy



Application

Elemental analysis by emission spectroscopy method which includes Fe, Al, Cu bases.

Range

Fe, Al, Cu, alloys

Tensile Testing Machine



Application

Measure the tensile strength, yield strength, elongation % and toughness in Steel, Aluminium (alloy), cast iron, copper (alloy), all metallic materials, plastic and rubber.

Range

0 - 250 KN

Residual Stress Measurement



Application

Detect residual stress during the manufacturing process of a material, or accumulated in a structure over many years in operation; helps predict the service lifetime of products.

Range

2θ from [[+98]]^° to [[+158]]^°

Electron Probe Measurement Analysis



Application

Used to non-destructively determine the chemical composition of small volumes materials; observation of the material structure; works similarly to a scanning electron microscope.

Range

All elements from B to U

Fourier Transform Infrared Spectroscopy



Application

Used to identify organic, polymeric, and in some cases, inorganic materials; identify compounds and the general type of the analyzed material when there are unknowns.

Range

7800-350*cm*-1

X-ray Fluorescence (XRF)



Application

Used to identify the chemical composition and elemental analysis of metals, glass, ceramics.

Range

All elements from B to U

Rubber Hardness Tester



Application

Measure the hardness of rubber parts in shore and IRHD scales.

Range

30-100 IRHD 0-100 DM

Humidity and Temperature Chamber



Application

Test the effect of a specified environment condition mainly on rubber and plastic materials.

Range

Humidity: ~98%

Temperature: -40 - 150°C

Geer Oven



Application

Test a wide range of materials: plastic, rubber, films, packaging materials, adhesives, etc. in aging simulation of temperature and air refresh.

Range

40 - 300°C

Salt Spray Tester (SST)



Application

The salt spray test is a standardized corrosion test method, used to check corrosion resistance of materials and surface coatings.

Range

Temperature: 35°C Max. sample size: 2000x1500x1200mm

Cyclic Corrosion Tester (CCT)



Application

Used to check the corrosion resistance of material and also evaluate the painting, plating and investigate the corrosion issues in fields.

Range

Temperature: -20 - 70°C Max. sample size: 2000x1500x1200mm

Test Item	Specific Test Performed	Range	Test Method	Material	
Hardness	Rockwell	20-88 HRA 20-100 HRBW 20-70 HRC	JIS Z 2245 ISO 6508	Ferrous metal; Steel, Cast Iron	
	Brinell	60-650 HBW	JIS Z 2243 ISO 6506	Non ferrous metal; e.g. Aluminum (alloy),	
	Vickers	100-850 HV	JIS Z 2244 ISO 6507	Copper (alloy)	
	Yield Stress			Ferrous metal; Steel,	
Tensile and Compression Strength	Tensile Strength	0-250 KN	U-25U KIN	JIS Z 2241 ISO 6892	Cast Iron Non ferrous metal;
	Elongation %			e.g. Aluminum (alloy), Copper (alloy)	

	Test Item	Specific Test Performed	Range	Test Method	Material
			"Fe" base material: C, Si, Mn, P, S, Cu, Al, Ni, Cr, Ti, Mo, V, Mg, Pb & Sn		Ferrous metal; Steel, Cast Iron
	Elemental Analysis (Chemical Composition)	Optical Emission Spectroscopy (OES)	"Cu" base material: Fe, Al, Si, Mn, P, S, Ni, Ti, Zn, Pb, Sn		Copper and Alloys
			"Al" base material : Fe, Cu, Si, Mn, P, Cr, Ni, Ti, V, Mg, Zn, Pb, Sn		Aluminum and Alloys
100		X-ray Fluorescence Analysis (wavelength dispersive/XRF)	All elements from B to U		Ferrous metal: Steel, Cast Iron Non ferrous metal; e.g. Aluminum (alloy), Copper (alloy)
		Energy Dispersive X (SEM/EDS)	All elements from Li to Cf Local analysis combined with SEM is possible		Ferrous metal: Steel, Cast Iron Non ferrous metal; e.g. Aluminum (alloy), Copper (alloy)

	Test Item	Specific Test Performed	Range	Test Method	Material
	Residual Stress Measurement	Residual Stress Test	2θ from[[+98]]^° to[[+158]]^°		Ferrous metal: Steel, Cast Iron
		Microstructure Observation	Magnification 1-1000X	ASM Handbook Vol 9	Ferrous metal: Steel, Cast Iron Non ferrous metal; e.g. Aluminum (alloy), Copper (alloy)
	Metallography	Grain Size Measurement		JIS G 5502	Steel
		Graphite size and distribution		ASTM E 112 ISO 643	Cast Iron
	Macrostructure Observation	Macrostructure Observation Weld Quality Check		JIS G 0553	Ferrous metal: Steel, Cast Iron Non ferrous metal; e.g. Aluminum (alloy), Copper (alloy)
	Depth of Decarburization	Measurement of Decarburization Depth	> 0.005 mm	ISO 3887 JIS G 0558	Steel



Test Item	Specific Test Performed	Range	Test Method	Material
Fractography (Fracture	Microscopic Observation	1x-540x	ASM Handbook	Ferrous metal: Steel, Cast Iron
Surface Analysis)	SEM Observation	20X-50000X	Vol 12	Non ferrous metal such as Aluminum (alloy), Copper (alloy)
Case Depth	Case Depth Measurement	0.1mm-10mm (HV0.01-HV5)	ISO 2636 JIS G 0557 SAE J 423	Case hardened/ induction hardened Steel
Crack	Penetration test (Color Check)		ISO 3452 JIS Z 2343	Ferrous metal: Steel, Cast Iron Non ferrous metal such as Aluminum (alloy), Copper (alloy)
Observation	Magnetic Test		ISO 9934 JIS Z 2320	Ferrous metal: Steel, Cast Iron



SCOPES: Plastic, Rubber, Adhesive, etc. Analysis

Test Item	Specific Test Performed	Range	Test Method	Material
	+			
Material Identification	Infrared Spectroscopy (FT-IR)	4000-400 cm-1		Rubber, Plastic, Adhesive, etc.
Hardness	International Rubber Hardness Degree (IRHD)	30-100 IRHD	JIS K 6253	Rubber
	Durometer	0-100 DM	ISO 48	
Elemental	X-ray Fluorescence Analysis (wavelength dispersive/ XRF)	All elements from B to U		
Analysis (Chemical Composition)	Electron Probe Micro Analyzer Analysis (EPMA)	All elements from B to U		Rubber, Plastic
	Energy Dispersive X (SEM/EDS)	All elements from Li to Cf Local analysis combined with SEM is possible		
Peeling Test	Peeling Test	0-50 KN	JIS K6854	Adhesive, Composite materials

MFTBC QM Material Lab Catalogue

SCOPES: Plastic, Rubber, Adhesive, etc. Analysis

Test Item	Specific Test Performed	Range	Test Method	Material
Tensile Strength	Yield Point Tensile Strength	0-50 KN	JIS K 6251 ISO 37 JIS K 7161 ISO 527	Rubber, Plastic
	Elongation %		JIS K 7171 ISO 178	
Heat Aging	Heat Aging Test	Temperature: 40-300°C Capacity: 600x600x600mm		Rubber, Plastic
Impact Resistance	Falling Ball Test Falling Parts Test	-30°C~RT Weight of Ball: ~500g		Plastic
Chemical Resistance	Chemical Resistance Test	Resistance to Acid and Alkaline Materials		Rubber, Plastic

AUTOGRAM

SCOPES: Plastic, Rubber, Adhesive, etc. Analysis

Test Item	Specific Test Performed	Range	Test Method	Material
Environmental Cyclic Test	Humidity and Temperature Cycle Test	Temperature: -40-150°C Humidity 20-98% Capacity: 1000x1000x800mm		Plastic
Flexural Test	Flexural properties	0-50 KN	JIS K7171	Plastic
Glass Fiber Content Measurement	Burning and Measuring Weight Test	2-10g	JISK7052	Plastic

MFTBC QM Material Lab Catalogue

SCOPES: Corrosion/ Paint Investigation

Test Item	Specific Test Performed	Range	Test Method	Material
Salt Spray Test (SST)	Salt Spray Test	Temperature 35°C NaCl: 5% Capacity: 2000x1500 x1200mm/150kg	JISZ2371 ISO9227 (MOD)	Painting, Plating
Combined Cyclic Corrosion Test (CCT)	Combined Cyclic Corrosion Test	Temperature: -20-70°C Humidity: 95% RH NaCI: 5% Capacity: 2000x1500 x1200mm/150kg		Painting, Plating





SCOPES: Corrosion/ Paint Investigation

Test Item	Specific Test Performed	Range	Test Method	Material
Material Analysis	Infrared Spectroscopy (FT-IR)	Wave Length Range: 4000-400 cm-1	JIS K5600 1-7 ISO2808	Painting
Painting Thickness	Thickness Test	0-800µm by Ultrasonic film thickness meter	JIS K5600 1-7 ISO2808	Painting
Plating Thickness	Microscopic Observation	Magnification 1-1000X	JIS H8501	Plating
Impact Test	Impact Test (DuPont Type)	Weight: 500g Height: ~50cm	JIS K5600 5-3 ISO6272	Painting
Coating Hardness	Pencil Hardness Test	6B~B, HB, F, H~6H	JIS K5600 5-4 ISO 15184	Painting
Painting Adhesion	Cross Cut Test	Grid Interval: 1mm or 2mm	JIS K5600 5-4 ISO 2409	Painting
Alkali/ Acid Resistance Test	Dipping or Spot Test	Resistance to Acid and Alkaline	JIS K5600 6-1	Painting/ Plating
Coating Hardness	Corrosion Pit Evaluation	Magnification 1-1000X	ASM Handbook Vol13	Plating, Aluminum

MFTBC QM Material Lab Catalogue

SCOPES: Corrosion/ Paint Investigation

Test Item	Specific Test Performed	Range	Test Method	Material
		 		
Visual Observation	Camera, Microscope Observation	1x-540x		Substance, Contamination
Elemental	X-ray Fluorescence Analysis (wavelength dispersive/ XRF)	All elements from B to U		Substance, Contamination
Analysis	Energy Dispersive X (SEM/EDS)	All elements from Li to Cf Local analysis combined with SEM is possible		Substance, Contamination
Material Analysis	Infrared Spectroscopy (FT-IR)	4000-400 cm-1		Substance, Contamination
Particle Size Distribution	SEM/EDS	200µm-	ISO16232 VDA19	Substance, Contamination

0000

MITSUBISHI FUSO TRUCK & BUS CORPORATION



10, Ohkura-cho, Nakahara-ku, Kawasaki-shi,

Kanagawa-ken, Japan 211-8522



MFTBC_qmlab@daimler.com



https://www.mitsubishi-fuso.com/en/

We look forward to working with you

